

**FB6018**  
**4-way screwed end ball valve**

Body: CF8M  
Ball: CF8M  
Seals: PTFE/RPTFE  
Pressure: Max. PN40  
Temperature: -20°C up to +150°C  
Size: 1/2"-4"



**FB6105**  
**2-Piece ball valve with butterfly handle female/male thread**

Body: CF8M  
Ball: CF8M  
Seals: PTFE/RPTFE  
Pressure: Max. PN64  
Temperature: -30°C up to +180°C  
Size: 1/4"-1"



**FB6205**  
**2-Piece ball valve with butterfly handle male/male thread**

Body: CF8M  
Ball: CF8M  
Seals: PTFE/RPTFE  
Pressure: Max. PN63  
Temperature: -30°C up to +180°C  
Size: 1/4"-1/2"



**FB6305**  
**2-Piece screwed end ball valve with spring return**

Body: CF8M  
Ball: CF8M  
Seals: PTFE/RPTFE  
Pressure: Max. PN64  
Temperature: -20°C up to +180°C  
Size: 1/4"-1"



**FC2005**  
**Piston check valve with butt weld end**

Body: CF8M  
Spring: CF8  
Seals: PTFE  
Pressure: Max. PN55  
Temperature: -30°C up to +140°C  
Size: DN15-DN80



# Valves



**Finsatec B.V.**

Buys Ballotstraat 13 · 7102EA Winterswijk  
The Netherlands  
info@finsatec.com · www.finsatec.com





Finsatec is a manufacturer of fittings in the area of industrial and housing technologies.

We meet highest quality standards with our extensive assortment of ball valves, exhaust valves and fittings.

We deliver valves for almost all areas of application in different material finishes.

Certified Quality of our products and a reliable service paired with an effective and modern logistics represent the philosophy of Finsatec.

Reliability and swiftness are virtues represented by all of our employees so that our customers will always get the best solution possible.

**FB6005E**  
**2-Piece ball valve**  
 Body: CF8M  
 Ball: CF8M  
 Seals: PTFE/RPTFE  
 Pressure: Max. PN63  
 Temperature: -30°C up to +180°C  
 Size: 1/4"-4"



**FB6007E**  
**3-Piece ball valve**  
 Body: CF8M  
 Ball: CF8M  
 Seals: PTFE/RPTFE  
 Pressure: Max. PN63  
 Temperature: -30°C up to +180°C  
 Size: 1/4"-4"



**FB6007ES**  
**3-Piece ball valve**  
 Body: CF8M  
 Ball: CF8M  
 Seals: PTFE/RPTFE  
 Pressure: Max. PN63  
 Temperature: -30°C up to +180°C  
 Size: 1/4"-4"



**FB6010E**  
**1-Piece wafer type ball valve**  
 Body: CF8M  
 Ball: CF8M  
 Seals: FKM/PTFE  
 Pressure: PN16/40  
 Temperature: -30°C up to +180°C  
 Size: 1/2"-4"



**FB6014A**  
**3-Piece flanged end ball valve with direct mounting pad**  
 Body: CF8M  
 Ball: CF8M  
 Seals: FKM/PTFE  
 Pressure: PN16/40  
 Temperature: -30°C up to +180°C  
 Size: 1/2"-5"



**FB6016**  
**Bibcock ball valve with hose coupler**  
 Body: CF8M  
 Ball: CF8M  
 Seals: NBR/PTFE  
 Pressure: Max. PN25  
 Temperature: -20°C up to +160°C  
 Size: 1/2"-1"



**FS1011**  
**Y-strainer**  
 Body: CF8M  
 Filter: CF8  
 Seals: PTFE  
 Pressure: Max. PN40  
 Temperature: -30°C up to +180°C  
 Size: 1/4"-3"



**FB6017**  
**High pressure 3-Piece ball valve**  
 Body: CF8M  
 Ball: CF8M  
 Seals: PTFE/RPTFE  
 Pressure: Max. PN200  
 Temperature: -30°C up to +180°C  
 Size: 1/2"-2"

